

PROTECTO WRAP SAFSEAL SYSTEMS



5500 PRIMER

DESCRIPTION

Protecto Wrap SafSeal Systems 5500 Primer is a high tack SBS rubber-based primer for use under the SafSeal 6000 and 7000 Series products, over Dens-Glass Gold[®], some OSB board, fire-treated plywood, metal, wood, dry concrete and dry masonry.

When used over Dens-Glass Gold, SafSeal 5500 Primer is moisture tolerant and is suitable for use on moist or damp Dens-Glass Gold. 5500 SB (solvent based) Primer is standard. 5500 WB (water based) Primer is available upon request.

SafSeal 5500 Primer is VOC compliant.

DIRECTIONS FOR USE

PREPARATION

- The surface shall be cleaned by brooming, vacuuming or high pressure clean dry air so that all dirt, dust, loose concrete, or other contaminants that may adversely affect the adhesion of the membrane are removed.
- Thinning of the primer is not recommended.

PROPERTIES

Adhesion to steel	Excellent
Adhesion to dry concrete	Excellent
Adhesion to dry masonry	Excellent
Adhesion to membrane	Excellent
Shelf life (min.)	One Year
Tack free time (minutes)	20-45 minutes
Specific Gravity	0.804
% Solids (by weight)	37
Flash Point	24°F

APPLICATION

- Apply primer to all surfaces by roller or brush.
- Primed surface shall be free of runs, puddles or excessive primer as this could cause blistering. Brush or roll out all primer puddles or drips immediately.
- Coverage is approximately 150 to 250 square feet per gallon, depending on the porosity of the substrate.
- Prime only as much area as can be covered in half a day's work. Re-prime areas not covered in half a day's work with a light coat of 5500 Primer.
- The opened containers, when not in use, should have the lids replaced to lessen the evaporation of the solvents.
- NOTE: Some bubbling in the primer may occur on the surface as it cures. This has no effect on the performance of the product and will smooth out as the membranes are applied.

PACKAGING AND WEIGHTS

QUANTITY	PACKAGING	WEIGHT
1 Gallon	4 gallons/carton	9 lbs.
5 Gallon pail	1 pail	46 lbs.



Protecto Wrap SafSeal Systems

1955 S. Cherokee St. • Denver, CO 80223
(800) 898-4842 • FAX (303) 777-9273
www.protectowrap.com