

PROTECTO WRAP SAFSEAL SYSTEMS



5535 MASTIC

DESCRIPTION

Protecto Wrap SafSeal Systems 5535 Mastic is an SBS modified rubberized asphalt liquid membrane for use in sealing around SafSeal Systems sheet waterproofing membranes in difficult to conform areas.

SafSeal 5535 Mastic can be used in conjunction with all SafSeal sheet waterproofing membranes, air/vapor barriers and flashing tape systems.

TYPICAL APPLICATIONS

For sealing around:

- Posts
- Protrusions
- Drains
- Support Braces
- Rebar
- Detail Cuts

PROPERTIES

Adhesion to steel	Excellent
Adhesion to dry primed concrete	Excellent
Adhesion to dry primed masonry	Excellent
Adhesion to membrane	Excellent
Shelf life (min.)	One Year

- Repairs and Patching in Waterproofing Membranes
- Membrane Terminations
- "T" Joints and End Laps

DIRECTIONS FOR USE

PREPARATION

- The surface must be cleaned and free from all dirt, dust, or any other foreign contaminants that may adversely affect the adhesion of 5535 Mastic.

APPLICATION

- Prime all metal, concrete and masonry surfaces prior to applying 5535 Mastic.
- 5535 Mastic is solvent based and should be used on top of SafSeal waterproofing systems.
- When using 5535 Mastic beneath any sheet membrane, 5535 Mastic must be allowed to fully cure prior to installing the membrane.

PACKAGING AND WEIGHTS

QUANTITY	PACKAGING	WEIGHT
1 Gallon	4 gallons/carton	43 lbs./carton
5 Gallon pail	1 pail	52.5 lbs.



Protecto Wrap SafSeal Systems

1955 S. Cherokee St. • Denver, CO 80223
(800) 898-4842 • FAX (303) 777-9273
www.protectowrap.com