



Premium Building Products
That Protect

PATENTED

Protecto Energy Plate Liner®



The only Self-Adhesive Air and Moisture Barrier between the Floor Deck and Wall Plate.

Protecto Energy Plate Liner® is designed specifically for conforming and sealing off the air gaps between the floor deck and the exterior wall plates.

The unique peel and stick adhesive bottom of **Protecto Energy Plate Liner®** allows for easy and precise placement. The 1/4" closed cell foam forms a gasket seal beneath the exterior wall plate virtually eliminating any air drafts resulting in a tremendous amount of heating and air conditioning energy savings.

ADVANTAGES:

- The only peel and stick 1/4" closed cell foam plate liner that totally stops air and moisture infiltration between the wood floor and wall plate.
- Can be used in residential, commercial and multi-family construction.
- Helps reduce energy costs by stopping air conditioning and heating loss between the wood floor and the wall plate.
- Self-adhering for easy and precise placement.
- Exceeds all local, state and national building codes.
- Conforms and seals off irregularities between substrates (i.e. warped wood to wood, metal frame to concrete, etc.).
- Convenient 3 1/2" and 5 1/2" widths.
- Stops dangerous carbon monoxide from entering the home from garage sill areas.
- Extremely resilient, will not rot or deteriorate with age.
- Adheres to wood, concrete, metal, block, vinyl and foam surfaces.



Premium Building Products
That Protect

Protecto Energy Plate Liner®

APPLICATION:

Areas to be sealed must be clean and dry. Align **Protecto Energy Plate Liner®** with the exterior perimeter of your floor deck. As you begin rolling out the **Protecto Energy Plate Liner®**, remove the release paper and press the adhesive bottom into place. Pressure is essential for gaining maximum adhesion to the substrate. Continue with your frame construction.

INSTALLATION BELOW 40°:

- Keep **Protecto Energy Plate Liner®** in a warm heated space above 60°F before use.
- Prime the top of the foundation with #100 Primer* and allow primer to tack up. Do not cover wet primer.
- Peel and stick the **Protecto Energy Plate Liner®** in place.

* Note: Protecto Wrap Protecto-Tak 16.25 oz. spray adhesive may be used in place of #100 Primer.

PACKAGING:

3¹/₂" x 25' rolls, 7 rolls per case, 24 cases per pallet

5¹/₂" x 25' rolls, 4 rolls per case, 30 cases per pallet

PROTECTO WRAP COMPANY

1955 South Cherokee Denver, Colorado 80223 (303) 777-3001 Fax (303) 777-9273 1-800-759-9727

www.protectowrap.com