



Premium Building Products
That Protect

Protecto Deck Flashing/Anti-Corrosion Tape



Eliminate unnecessary repairs on your new deck and water damage that causes premature wood rot and decay. The use of **Protecto Deck Flashing/Anti-Corrosion Tape** will add years to the life of your deck. **Protecto Deck Flashing/Anti-Corrosion Tape** is a 40 mil thick, flexible peel and stick waterproofing membrane tape that is intended for use as a waterproof/anti-corrosive barrier between ACQ/AC2 treated lumber and metal surfaces. This product can be used to protect anywhere ACQ/AC2 lumber is used, including between metal hangers, sill plate, and deck plates.

FEATURES AND BENEFITS:

- Easy to install peel and stick application
- Protects joists from wood rot damage due to water infiltration
- Creates a corrosion barrier between ACQ/AC2 treated lumber and non ACQ/AC2 approved metal surfaces
- Use of Protecto Deck Flashing/Anti-Corrosion Tape as a ledger board flashing eliminates moisture between the house and ledger board
- UV Resistant
- Self seals around nails and screws



INSTALLATION:

- Surface area needs to be clean and dry of any foreign material.
- No nails or screws are necessary for flashing tape application, but if they are used, the material will self seal around the fasteners.
- Temperature application works best at 45 degrees or warmer. If application is below 45 degrees, the use of Protecto-Tak Spray Adhesive or similar product is recommended.
- Measure and cut Protecto Deck Flashing/Anti-Corrosion Tape to desired length.
- For use on joist, center tape over joist, peel off release liner and press into place. Extend membrane over top and down sides of joist, ledger board, or beams.
- When applying to metal or wood surfaces and used as an ACQ/AC2 barrier, overlaps need to have a minimum of 2" overlap for end to end, and a minimum 1" overlap for side to side applications.

PRECAUTIONS:

To prevent premature corrosion, Protecto Deck Flashing/Anti-Corrosion Tape should be applied to all locations where the galvanized metal connectors and hangers are in direct contact with the ACQ/AC2 and other treated wood products.

Protecto Deck Flashing/Anti-Corrosion Tape may be incompatible with certain sealants and caulking that contain solvents. Solvent-free caulking should be used in conjunction with Protecto Deck Flashing/Anti-Corrosion Tape.

Some fasteners may be incompatible with ACQ/AC2 and other treated wood products. Please refer to hanger manufacturers' recommendations when selecting fasteners to attach hangers to ACQ/AC2 and other treated wood products through Protecto Deck Flashing/Anti-Corrosion Tape.



Protecto Wrap Company
(800) 759-9727
www.protectowrap.com

Premium Building Products
That Protect

