



***Protecto Wrap Company is pleased to introduce our NEW Protecto Flex Window and Door Tape. This product allows the ease of application in waterproofing curved or radius door and window installations.***

Protecto Flex is a 60 mil thick peel and stick flashing tape. The flexible cross laminate top surface will expand and conform to irregular or curved surfaces while the aggressive adhesive adheres to form a permanent bond between the window fin and the building substrate. Protecto Flex gives you a total air and water seal without having to cut and patch in the membrane to conform to the door and window opening.

Protecto Wrap Company's Protecto Flex is suitable for sealing the following applications:

- Window and door perimeters to the building substrate
- Joints in stucco applications
- Sheet rock joints
- Other areas where a water or air seal is needed

#### **Advantages:**

- Protecto Flex can expand and conform to radius or curved window fins
- Aggressive adhesive forms a permanent bond between the window fins and the building substrate
- Ease of application — just peel and stick — no fasteners required
- Self seals around nails, screws and staples used to secure housewraps and building paper
- Adheres to plywood, OSB, vinyl, polyethylene, aluminum, metal, foam, concrete and masonry surfaces
- Protecto Flex may be left exposed up to 120 days
- Protecto Flex has the most aggressive adhesive of any flashing tape
- Backed by over 50 years of manufacturing expertise of the finest waterproofing membranes available on the market today

**Only Protecto Wrap Offers a Single Source Waterproofing/Weatherproofing System.  
From the Footing of the Foundation to the Peak of the Roof.**

## Application:

1. Surfaces should be clean, dry and free of dirt and other foreign materials. Protecto Flex eliminates the need for sealant or caulk. Do not use any solvent-based sealant on or around Protecto Flex Tape.



2. For temperatures below 45°F (7°C) the material must be stored in a warm area prior to use and must be used with Protecto Wrap's Protecto-Tak Spray Adhesive or BT-Primer. All OSB must use primer or spray adhesive.



3. Cut a piece of Protecto Flex Window Sealing Tape in a length that covers the bottom flange extending 2" past the side of the window.



4. Remove approximately 4" of release paper and begin adhering Protecto Flex Tape to the bottom of the window flange while removing release paper. Smooth the Protecto Flex Tape as the adhesive back comes into contact with the window fin and building substrate.



5. Cut a piece of Protecto Flex Window Sealing Tape long enough to cover the radius of the window extending past the bottom of the window a minimum of 2" on each side.



6. Remove approximately 4" of release paper and begin adhering Protecto Flex Tape to the side of the window flange while removing release paper, smooth the Protecto Flex Tape as the adhesive back comes into contact with the window fin and building substrate. Protecto Flex Tape can expand and follow the contours of a radius window while completely sealing off the window fin to the building substrate.



7. Trim any excess Protecto Flex Tape from the window area.



## Availability:

| Roll Widths | Rolls Per Case | Cases Per Pallet |
|-------------|----------------|------------------|
| 4" x 50'    | 12             | 18               |
| 6" x 50'    | 8              | 18               |

*Other sizes are available upon request.*

## Physical Properties:

|                       |  |
|-----------------------|--|
| Color                 | White/Gray                                   |
| Thickness             | 60 mils                                      |
| Elongation            | 500% min. (rubberized asphalt adhesive only) |
| Permeance             | .01 perms max ASTM E-96                      |
| Maximum Exposure Time | 120 Days                                     |



Premium Building Products  
That Protect

**Protecto Wrap Company**  
1955 South Cherokee St.  
Denver, CO 80223  
800.759.9727 fax 303.777.9273  
[www.protectowrap.com](http://www.protectowrap.com)