

PROTECTO PATCH

FOR USE WITH PROTECTO CMU100 WATER RESISTANT COATING AND PROTECTO LWM200 LIQUID WATERPROOFING MEMBRANE



Premium Building Products
That Protect

Protecto Patch is designed to fill cracks and voids up to 1/4" in concrete and masonry applications and is for use with Protecto CMU100 Water Resistant Coating and Protecto LWM200 Liquid Waterproofing Membrane.

BENEFITS

- ◆ Tested by SGS US Testing Company
- ◆ Contains anti fungal ingredients
- ◆ Contains rust inhibitors
- ◆ Can be applied to dry or damp walls
- ◆ Can be painted or coated over
- ◆ Requires only one application
- ◆ Non toxic, non flammable
- ◆ Standard color is tan

LIMITATIONS

Do not let product freeze. Store indoors at temperatures above 32°F. It is recommended that the temperature should be 28°F and rising before application. Do not dilute Protecto Patch. Do not apply Protecto Patch on glazed tile, slate, glazed brick construction, acrylics or painted finishes. Protecto Patch is designed to be used as a waterproofing material to stop moisture penetration caused by cracks or holes in the surface that are less than 1/4" in diameter or width. KEEP OUT OF REACH OF CHILDREN.

NOTE

Always perform a job site test to ensure desired results.

APPLICATION

Protecto Patch is designed to fill cracks and voids up to 1/4" in concrete and masonry applications and is for use with Protecto CMU100 Water Resistant Coating and Protecto LWM200 Liquid Waterproofing Membrane.

CMU100 & LWM200 may be applied directly over uncured Protecto Patch.

WARRANTY

Protecto Wrap Company expressly warrants, subject to the Exclusion of Warranties provision set forth below, that its products shall be fit for the ordinary purposes for which such products are intended for a period of ten (10) years. NO OTHER EXPRESS WARRANTIES AND NO IMPLIED WARRANTIES including implied warranties of MERCHANTABILITY and/or fitness for a particular purpose shall be applicable to any product(s) of Protecto Wrap Company, except to the extent that any of such products are specifically covered by an expressed warranty that is provided in writing to a particular purchaser by an authorized employee of Protecto Wrap Company.

In the event of a breach of any product warranty extended by Protecto Wrap Company, Protecto Wrap Company's liability and the associated claimant's sole and EXCLUSIVE REMEDY is EXPRESSLY LIMITED to the repair or replacement of the defective product(s) FOB Denver on a pro rata basis according to the original sale price, so that the claimant will effectively be charged only for that portion of the normal useful life of the defective product(s) which has elapsed since the purchase date of the product(s). Under no circumstances shall Protecto Wrap Company be liable for any consequential damages, including any labor costs that may be associated with a breach of any product warranty extended by Protecto Wrap Company.

EXCLUSION OF WARRANTIES

Protecto Wrap Company assumes no warranty regarding the installation of its products. In addition, if Protecto Wrap Company's products are not properly installed, then no product warranties, expressed or implied shall apply to the products that have been improperly installed.

TECHNICAL SERVICES

Technical advice furnished by Protecto Wrap Company concerning any use or application of Protecto Patch is reliable as current technology allows. Protecto Wrap Company makes no warranty, expressed or implied, of any use of application for which such advice is furnished.

TECHNICAL INFORMATION

Properties	Test Method	Test Results
Hydrostatic Pressure Over Cracks	ASTM C 836-95	35.45 Bursting Pressure (ft. H ₂ O)
Low Temperature Flexibility & Crack Bridging	ASTM 836, Section 6.7	No cracking or damage was observed
Resistance to Water	ASTM D 2939, Section 15	No softening or loss of adhesion
Water Vapor Transmission	ASTM E 96	6.181 (g/h-M ²) 13.14 Perms (in-lbs)
Color Fastness of Surface Coating	ASTM D 2565	No change was observed after 1000 hours of exposure
Resistance to Mold Growth	ASTM D 3273-94	No mold growth was observed

Drying time @ 77°F, 50% RH:

Temp & humidity dependent
Touch: within an hour

Regulatory Information

US Federal regulations:

O.S.H.A.:

CERCLA:

Vehicle Type:

VOC:

Exempt from TSCA

Non Hazardous

Noncarcinogenic Hazard Section 313

Acrylic blend

Contains < 190 gm/l voc



Premium Building Products
That Protect

PROTECTO WRAP COMPANY

(800) 759-9727

www.protectowrap.com



BUILT GREEN.

Protecto Patch Rev 9/27/07